

PRODUCT REQUIREMENT SHEET

See LV-75-34



ELECTRICAL DATA
(with the specified ballast)

	Measuring Point	Value	Unit	Tolerance
Lamp Wattage	0h	1000	W	Nom
Lamp Voltage	0h	100	V	-8/+15
Lamp Current	0h	12.3	A	Nom
Power Density	0h	NA	W/cm	Nom
Ignition Supply Voltage	0h	198	V	min
Ignition Time	0h	1	s	Max
Warm-Up Time		0.5	min	Max
Re-Ignition Time		0.5	min	Max

UV RADIATION
(with the specified ballast)

	Measuring Point	Value	Unit	Tolerance
UV-A (315-400 nm)	0h	NA	μW/cm ²	± 10%
UV-B (280-315 nm)	0h	NA	μW/cm ²	± 10%
UV-C (200-280 nm)	0h	NA	μW/cm ²	± 10%
DIAZO (350-460 nm)	0h	NA	μW/cm ²	± 10%
UV Maintenance	750h	NA	%	min
Doping	Xenon Lamp			
Quartz Tube	Ozone free			

GENERAL SPECIFICATIONS
(in operating conditions)

	Value	Unit	Tolerance
Bulb Temperature	750 950	°C	min Max
Pinch Temperature	350	°C	Max
Lamp Position	Any		

BALLAST DESCRIPTION

Ballast Reference	BSN1000		
Ballast Power (indicative)	1000 W	Supply Voltage	220 V
Supply Wave Form	Sine wave	Frequency	50 Hz
Ignitor Reference	SN56	Capacitor Reference	No μF

1	0833	2	0833	3	0000	4	m : xxx g	5		6		7		8	
SUPERSEDES :		UV LAMP						9283 001 05100			29/08/2016				
New		DrF-X-15-A						0833/000							
REF. :	PDM UV-378	DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10			A4				
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															