

## 187A.VE - 1,000 Volt insulated combination pliers



### **Standards:**

**NF ISO 5746, ISO 5746, DIN ISO 5746, ASME B107.500, NF EN 60900, EN 60900, DIN EN 60900**

### **Description:**

- For your safety, all pliers are tested individually at 10,000 volts for 10 seconds, at the end of the manufacturing cycle.
- Serrated flat and oval pipe/cable gripping surfaces combined with a high performance cutting edges.
- Cutting edges designed to cleanly cut all types of wire: soft wires and modern materials to a maximum piano wire specification of: - 187A.16VE : 1.8mm 215 kg/mm<sup>2</sup> - 187A.18VE : 2.0mm 210 kg/mm<sup>2</sup>
- High mechanical advantage due to off-set rivet and cutting edge geometry reducing effort.
- High durability carbon alloy steel, with induction hardened cutting edges.
- Bi-Material ergonomic grips resistant to chemical agents featuring: - Return spring - Tether ready (Tether point adds 10mm to nominal length)
- Varnish finish to help prevent rusting.

## Informations:

	Length L [mm]	Thickness E [mm]	Head Height C [mm]	Head Width B [mm]
<b>187A.16VE</b>	165.0	9.5	34.0	21.0
<b>187A.18VE</b>	185.0	10.0	36.0	23.0