


## ECLAIR 36W 24V façade lamp




Power	<b>36 W</b>	Voltage	<b>24 V</b>
Luminous flux*	<b>2000 lm (90°)</b>	Colour of light	<b>WW</b>
Beam angle	<b>45 °</b>	Degree of protection (IP)	<b>IP65</b>



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI001013WW
Power	36 W
Nominal current	1500 mA
Voltage	24 V
Energy efficiency class	G
Energy consumption	40 kWh/1000h
Frequency	DC Hz
Protection class	III
Power supply included	-
Power factor	1
Useful luminous flux*	2000 lm (90°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	55 lm/W
Colour of light	WW
Beam angle	45 °
Light source included	+
Uniformity of color SDCM max	6
Dimmable	+
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	1000x43x85 mm
Weight	2.15 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Number of pieces on the packaging	12 pcs.
Made in	PRC



\*applies to the LED source used, \*\*Luminaire luminous flux