

REVAMP1120T

1-channel 100V digital power amplifier, 1 x 120W



Our newest single channel professional power amplifier the REVAMP1120T is a unique and versatile Apart design with 1 x 120 watts output power @ 100 volts (or @ 4 ohms). The REVAMP1120T is a class-D amplifier with a built-in galvanic separated toroidal output transformer free of external influences and disturbances. Convection-cooled and excluded from cooling fans this amplifier is reliable, maintenance-free, silent and dust-free.

The rear clip LED indication on the input gain together with the ease of installation via multiple input and link connection options make the REVAMP1120T the preferred installer's choice. Completely built in a 1U chassis without front control the REVAMP1120T is bound to become a reference in the small and mid-sized fixed install audio market.

TECHNICAL SPECIFICATIONS

| | | | |
|--------------------------------------|-----------------------------------|--|-----------------------------|
| dynamic output power 4 ohms in watts | 120 | RMS output power 4 ohms in watts | 120 |
| dynamic output power 8 ohms in watts | 60 | RMS output power 8 ohms in watts | 60 |
| output power RMS 100 volts in watts | 120 | minimum impedance load per channel in ohms | 4 |
| power consumption (max) in watts | 200 | 19" (483 mm wide) rack mounting | yes |
| height- rack units (1U=44 mm) in U | 1 | height in mm | 44 |
| depth (build in) in mm | 230 | depth (incl front) in mm | 239 |
| power supply | 115 - 230 VAC | power supply technology | switching mode power supply |
| output voltage tapings | 100 - 70 - 50 - 35 volts - 4 ohms | output channels | 1 |
| line input balanced | 1 | line input unbalanced | 1 |
| channel separation | > 65 dB @ 1 kHz | power amp topology | class-D |
| frequency response (in Hz) | 50 - 20 k | cooling system | convectional |
| applicable in 100V | yes | applicable low impedance | yes |
| Net weight product (kg) | 4.6 | | |

MORE PICTURES

