



No. 1 Houghton Hill Industries
Sawtry Way
Houghton, Huntingdon,
Cambridgeshire
PE28 2DH
England

Tel: +44 (0)1480 494540
Fax: +44 (0)1480 494206
Email: Info@lemark.co.uk
Web: www.lemark.co.uk

Black Felt Tape Adhesive

Product Description

Solvent-free environmentally friendly double-sided adhesive tape with special paper carrier and dispersion acrylic adhesive.

Product advantages

Pressure sensitive adhesive tape with excellent initial adhesion (tack) and cohesion.
Good resistance to ageing and UV radiation.
The outstanding viscoplastic adhesive formulation makes the tape particularly suitable for material surfaces with large open pores.

Main application fields

Self-adhesive preparation of plastics, metal, paper, ceramics, textiles, foams and felts.
Used in the manufacture of carpet trims.

Specification Approvals

Ford WSS-M99P9999-A1
Renault 00-10-150
Opel Q 00001
VW 50115

Technical data

Adhesive:	Dispersion pure acrylic
Carrier:	Special paper
Interliner:	Brown silicone paper
Thickness:	approx 0.14mm
Temperature range:	-40°C to +120°C

Shear strength on steel in accordance with DIN EN 1943 (N/625 mm ²)	+ 23°C +/- 2°C 9
---	------------------

Peeling on steel in accordance with DIN EN 1939 (N/25 mm)	+ 23°C +/- 2°C 30
---	-------------------

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50 – 70%).

Disclaimer

PLEASE NOTE: Stated performance figures and specification are based on average values and should not be regarded as maximum or minimum values. Measurements are approximate. Due to the nature of this product, performance may deteriorate over time. Due to varying application environments, the suggested uses should be considered as a general guide only. We recommend all users assess the suitability of our products for their individual application.

